DERWENT ABSTRACT FOR: JP 04-028739 (Mitsubishi), published 31 Jan 1992:

L1 ANSWER 5 OF 9 WPINTEX COPYRIGHT 2001 DERWENT INFORMATION LTD

ACCESSION NUMBER: 1992-085306 [11] WPINDEX

DOC. NO. CPI

C1992-039266

TITLE:

Thermoplastic resin compsn. prepn. - by blending

polyolefir resin, polyphenylene ether resin and polymer having alkenyl aromatic and aliphatic hydrocarbon polymer

chair..

DERWENT CLASS A12 A17 A25
PATENT ASSIGNEE(S): (MITP) MITSUBISHI PETROCHEMICAL CO LTD; (TOYT) TOYOTA

JIIOSHA KK

COUNTRY COUNT

1

PATENT INFORMATION:

PATENT NO KIND DATE WEEK LA PG _________ JP 04028739 A 19920131 (199211)* 11 <--

APPLICATION DETAILS:

PATENT NO	KIND	APPLICATION	DATE
JP 04028739	A	JP 1990-133749	19900525

PRIORITY APPLN. INFO: JP 1990-133749 19900525

1992-035:06 [11] WPINDEX

JP 04028739 A UPAB: 19931006 AB

Compsn is prepd. by blending component (B) and 20% or more of component (2) to obtain a composit. (I), and then blending (I) with component (A) and the remaining (C). (A) is polyplefin resin 30-78 wt.%, (B) is polyphenylene-ether resin 20-63 wt.% and (C) is 2-50 wt.% polymer having both alkenyl aromatic cpd. polymer chain (C1) and aliphatic hydrocarbon polymer chain (C2) per molecule and dynamic shearing modulus at 23 deg.C of 3 x 10 power 8 dyne/cm2 or higher.

(A) is isostatic polypropylene. (C) is partially hydrogenated alkenyl cpd.-conjugated diene block copolymer such as hydrogenated styrene-butadiene triblock copolymer.

ADVANTAGE - Compsn. has good mechanical properties, esp. a good talance between impact strength and rigidity.